


For further information, please scan the QR code.


Structure Illustrations




⊗ Installation Application



① Hanging Installation



② Support pole installation



③ Monitor Installation

📊 Acoustics

| | FS10 | FS12 |
|--------------------|-----------------------------------|-----------------------------------|
| Power | 320W (AES) | 450W (AES) |
| Program power | 640W | 900W |
| Nominal impedance | 8 Ω | 8 Ω |
| Frequency response | 55~20kHz | 50~22kHz |
| Sensitivity | 98dB/W/m (wideband 200~16000Hz) | 98dB/W/m (wideband 200~16000Hz) |
| Maximum SPL | > 125dB | > 127dB |
| Horizon | 80°above 1500Hz | 80°above 1500Hz |
| Vertical | 50°above 1500Hz | 50°above 1500Hz |
| LF driver | 1X10" Custom made European driver | 1X12" Custom made European driver |
| Voice coil | 2.5" | 3" |
| HF driver | 1X1" Custom made European driver | 1X1" Custom made European driver |
| Voice coil | 1.7" | 1.7" |
| N.W/G.W | 18kg / 23kg | 19kg / 24kg |
| Product Dimensions | W330xH560x342mm | W356xH600xD370mm |

📊 Acoustics

| | FS15 |
|--------------------|------------------------------------|
| Power | 500W (AES) |
| Program power | 1000W |
| Nominal impedance | 8 Ω |
| Frequency response | 42~18kHz |
| Sensitivity | 99dB/W/m (wideband 200~16000Hz) |
| Maximum SPL | > 131dB |
| Horizon | 70°above 1500Hz |
| Vertical | 50°above 1500Hz |
| LF driver | 1X15" Custom made European driver |
| Voice coil | 3" |
| HF driver | 1X1.4" Custom made European driver |
| Voice coil | 3" |
| N.W/G.W | 28kg / 34kg |
| Product Dimensions | W445xH730xD425mm |

🔌 Connector

2x NEUTRIK® NL4MP(1+/1-Link, 2+/2-Input & Link)

📦 Cabinet

CNC made 18mm birch wood sandy wear-resisting environmental polyurea spray paint

🔗 Hanging side frame

14x M8 flying points